

# CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

Certificate No.:  
2388-CPR-24-79411 Rev. 0.0

Initial certification date:  
29.04.2024

Validity end date:  
29.04.2027

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product(s)

**Structural products of Aluminium and aluminium alloys for construction works**  
to be use in metal structures or in composite metal and concrete structures

placed on the market under the name or trade mark of

**Hydro Extrusion Hungary Kft.**

Verseci út 1-15, 8000 Székesfehérvár, Hungary

and produced in the manufacturing plant(s)

**Hydro Extrusion Hungary Kft.**

Verseci út 1-15, 8000 Székesfehérvár, Hungary

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

**EN 15088:2005**

under system 2+ are applied and that

**THE FACTORY PRODUCTION CONTROL IS ASSESSED TO BE IN CONFORMITY WITH  
THE APPLICABLE REQUIREMENTS**

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

For more details see Appendix accompanying this Certificate.

Place and date:  
Barendrecht,, 29-04-2024

For the issuing office:  
Notified Body 2388, The Netherlands

Check Validity



Bjørn Spongsveen  
Management Representative

# Appendix to Certificate

## Certificate history:

Revision	Description	Issue Date
[0.0]	Original Certificate	2024.04.26

## Additional information to the scope of certificate

<b>Product Standard</b>	EN 755-1/2 and EN 12020-1:2022
<b>Product(s)</b>	Extruded Products ; Tubes and Profiles; Extruded Precision Profiles
<b>Dimension Standard</b>	EN 755-3:2008; EN 12020-2:2016 +AC:2017

**Designation:** Aluminium Alloys: AW- 6005A; AW 6060; AW 6063; AW 6082

Grade	Temper Condition	Width/Section/Mould size		Thickness(mm)		Length(mm) / Weight (Kg) max.
		min.	max	min.	max	
EN-AW 6005A	T4, T6	0.8	80	10	500	8000 mm/ 20kg/m
EN-AW 6060	T4, T6, T66	0.8	80	10	500	8000 mm/ 20kg/m
EN-AW 6063	T4, T5, T6, T64, T66	0.8	80	10	500	8000 mm/ 20kg/m
EN-AW 6082 Extruded Products ; Tubes and Profiles	T4, T5, T6	0.8	80	10	500	8000 mm/ 20kg/m
EN-AW 6060	T4, T6, T66	0.8	80	10	500	8000 mm/ 20kg/m
EN-AW 6063 Extruded precision profiles	T4, T5, T6 T66, T64	0.8	80	10	500	8000 mm/ 20kg/m

## Declaration of performance and marking of product

When meeting with the terms and conditions, as required, the manufacture shall draw up an EC declaration of product performance and legally affix the CE mark followed by the notified factory production control certification body identification number of DNV (2388).

End of Certificate